

# COMMANDER

## ADA Compliant Heavy Duty Door Opener

### Features

- ★ Non handed unit
- ★ Easy, self programming setup
- ★ Built in safety feature reverse on obstruction
- ★ Quiet operation
- ★ Complies with ANSI A156.19 for Low Energy Swing Door Openers and ANSI 156.10 for Full Energy Automatic Door Openers
- ★ UL Certified for use as fire door operators (3 hour rating)
- ★ Complies with all US and Canadian ADA requirements
- ★ Power Close for wind or positive pressure applications
- ★ Built in Electric Lock relay and accessory power I/O terminals
- ★ Push and go activation (can be enabled or disabled in settings)
- ★ Power assist close
- ★ Slim 4-1/8" Tall x 4-3/4" Depth Profile



**MADE IN USA**



**3 HOUR FIRE RATED**



**ADA & UL LISTED  
COMMERCIAL**



**OBSTRUCTION  
SAFETY REVERSE**



**SELF PROGRAMMING  
SET UP**

### Activation Accessories



**HARDWIRED  
ACTIVATION  
BUTTON**



**WIRELESS  
ACTIVATION  
BUTTON**



**WEATHERPROOF  
ACTIVATION  
BUTTON**



**ADA DOOR MOUNTED  
SENSOR**



**WEATHERPROOF  
BOLLARD  
WITH WIRELESS  
BUTTON**



**36" VERTICAL  
ACTIVATION  
BUTTON  
WIRELESS OR  
HARDWIRED**




**WIRELESS  
& TOUCHLESS  
ACTIVATION  
BUTTON**



**HANDHELD FOB  
WIRELESS  
TRANSMITTER**

### Security Accessories



**ELECTRIC STRIKE  
FOR CYLINDRICAL  
LEVERS**



**ELECTRIC STRIKE  
FOR RIM EXIT DEVICES**



**ELECTRONIC  
KEY PAD**

## AUTOMATIC DOOR AND HARDWARE

[CUSTSVC@AUTODOORANDHARDWARE.COM](mailto:CUSTSVC@AUTODOORANDHARDWARE.COM)

# COMMANDER

## ADA Compliant Heavy Duty Door Opener

### Specifications

Power Supply	115 VAC $\pm$ 6%		
Power Consumption	100W		
Current Consumption	1A		
Motor	24 VDC		
Header Dimensions	4-1/8" Tall x 4-3/4" Depth		
Fused Protection	3.5A Fuse (F1 located on I/O Board)		
Weight	22 lbs (single), 45 lbs (dual)		
Operating Temperature	-4° to 131° F		
Ingress Protection	IP23 (protection from rain)		
Maximum Door Weight	Door Size	Push Arm	Pull Arm
	36"	438 lbs	342 lbs
	42"	328 lbs	256 lbs
	44"	299 lbs	234 lbs
	48"	254 lbs	198 lbs
Accessory Power Supply	24VDC / 1A Maximum		
Electric Lock Power Supply	24VDC / 1A Maximum		
Adjustable Speeds and Timers	Opening Speed Closing Speed Hold Open Time Closing Speed with Power Off		
Switch Functions	Automatic Hold Open Manual (Off)		
Control Outputs	Malfunction Alarm Signal Electric Lock Relay 24 VDC Accessories Power Supply Door Status		
Control Inputs	Interior Activation Exterior Activation Emergency Shutdown Alarm Output "Stop" Safety Device (door-mounted) Safety Device Input Secondary Activation		



**OBSTRUCTION  
SAFETY REVERSE**



**SELF PROGRAMMING  
SET UP**



**3 HOUR FIRE RATED**



**ADA & UL LISTED  
COMMERCIAL**

The Commander Door Opener by Automatic Door and Hardware is your ADA solution to any building entrance. The Commander ADA door opener is designed with everything you need to meet full ADA compliance. It also features a 3 hour fire rated door compliance, allowing it to be installed on virtually any commercial building doors. Where other door openers lack these abilities, the Commander excels.

The advanced design of the Commander allows it to be robust and powerful in a slim header body. The small size allows the Commander to be installed on hollow metal steel door frames, storefront door frames, and wood door frames with ease.

## AUTOMATIC DOOR AND HARDWARE

CUSTSVC@AUTODOORANDHARDWARE.COM